

USB 3.2 Front Panel 4 Port Hub - 5Gbps - 3.5in Bay

Add a 4-port SuperSpeed USB 3.2 Gen 2 5Gbps Hub to the 3.5" front bay opening of a computer case

Model No.: USB35-2A2C-5G

Version: v1.0

| 3.5" Front Panel | 4-Port 10Gbps Hub | USB 3.2 Gen 1 Type-A | USB 3.2 Gen 1 Type-C | 5Gbps |

The flykantech.com USB35-2A2C-5G 3.5-inch Front Bay to 4-Port USB 3.2 Gen 1 Panel Hub – a versatile solution that effortlessly converts any available 3.5-inch computer case front bay into a high-performance 4-Port USB 3.2 Gen 1 5Gbps hub. This sleek hub features two USB 3.2 Gen 1 Type-A ports and two USB 3.2 Gen 1 Type-C ports, ensuring seamless connectivity.

Effortlessly expanding your system's capabilities, this front panel hub requires just a single USB connection, adding four convenient USB ports to the front of your computer case. For compatibility with a 5.25-inch bay, you can use the optional Front Bay Bracket Adapter accessory (sold separately). Each added port adheres to the USB 3.2 Gen 1 standard, providing up to 10 Gbps of high-speed bandwidth. The USB35-2A-2C-5G is powered by a 4-Pin LP4 cable, and data exchange is facilitated through the included 5G USB 3.2 Gen 2 Type-A to USB Type-E Cable. It is compatible with OS Independent, requiring no additional drivers or software for seamless operation.



Applications

- Expand your system's USB 3.2 Gen 1 with additional ports for connecting high speed external storage devices
- Enhance accessibility by adding USB ports to the front of your computer system.
- Utilize an internal USB port and an unused 3.5-inch front bay to boost system expandability.

Main Features

- Upgrade your PC's front bay to a 4-Port USB 3.2 Gen 1 hub.
- Fits into any 3.5" computer case front bay
- Features 2 USB 3.2 Gen 1 Type-A and 2 Type-C ports.
- Convenient front panel design for easy access.
- Supports up to 10 Gbps bandwidth with USB 3.2 Gen 1.
- OS Independent; No additional drivers or software required
- **ODM is available**

**Product appearance & specifications are subject to change without notice.*

Specifications

External Ports	2 x USB Type-A, 2 x USB Type-C
Internal Ports	1 x 4-Pin LP Power Connector
	1 x 10G USB 3.2 Gen 1 Type-A
Type and Rate	USB 3.2 Gen 2 10Gbps
Fast-Charge Port(s)	No
Form Factor	Drive Bay
Material	Metal
Power Source	USB-Powered / 4-Pin Powered
Operating Temperature	5°C to 50°C
Storage Temperature	-10°C to 60°C
Humidity	20% ~ 80% RH
Accessories Packed in a Brown Box (16 x 13 x 3cm)	
1. 1 x USB35-2A2C-5G 1 x USB 3.0 to 19PIN 3. 6 x Mounting Screws	



Fly Kan Tech Co., Limited (HK) | Shenzhen VTOP Electronic Co., Limited(Mainland)
Tel: +86-755-85288085 Fax: +86-755-85288085 Email: sales@flykantech.com

<https://www.flykantech.com>

USB35-2A2C-5G

Updated on 2024/03/12