

# Mini DisplayPort to HDMI Converter - 4K 30Hz Video

Eliminate clutter by connecting your Mac or PC directly to an HDMI display using this short cable

Model No.: mDP2HD430-I

Version: v2.0

## | mDP to HDMI Video Converter | mDP 1.2 to HDMI Adapter Dongle | Mini DP or Thunderbolt 1/2 Mac/PC to HDMI |

The mDP2HD430-I Mini DisplayPort to HDMI adapter cable connects Mini DisplayPort devices like Microsoft Surface Pro, MacBook, or Ultrabook laptops to HDMI displays or projectors. This passive adapter supports up to Ultra HD 4K resolutions and is Thunderbolt compatible when connected to a supporting DisplayPort over Thunderbolt I/O port.

Maintaining exceptional picture quality at four times the resolution of 1080p, the mini DisplayPort to HDMI adapter ensures a superior viewing experience and is backward compatible with lower resolution displays. Supporting HD resolutions of 1080p and 720p, it helps future-proof setups for 4K video.

For a straightforward installation, the mDP to HDMI adapter connects directly from your Mini DisplayPort video source to the HDMI port on your display. Unlike some converters, it doesn't require a power source, simplifying the setup process. The compact design of the mDP2HD430-I ensures a tidy and professional installation by eliminating excess cables.



### Applications

- Carry the adapter for quick HDMI connections at trade shows or in hotel rooms during your travels.
- Link your laptop to HDMI-equipped hot desks or boardroom projectors effortlessly with the portable adapter.
- Transform your HDMI monitor into a secondary display for increased flexibility and productivity.

### Main Features

- Supports 4K 30Hz (3840x2160) , Audio (via HDMI)
- Backward compatible with 1080p
- Uni-directional, Not Bidirectional
- Supports Thunderbolt 1 & 2 (\*\*Important Notice)
- Plug-and-play installation
- No power adapter required

*\*Product appearance and specifications are subject to change without notice.*

### Specifications

Connector(s)	Input: Mini DisplayPort (Male) Output: HDMI Type A (Female)
Interface Standard	DisplayPort 1.2, HDMI 1.4
Max. Input Resolution	3840x2160@30Hz
Max. Output Resolution	3840x2160@30Hz
Audio Support	via HDMI
Housing/Jacket Material	ABS/PVC
Operating Temperature	0°C to 70°C
Storage Temperature	-10°C to 70°
Humidity	10%-85% (non-condensing)
Dimensions (approx.)	40 x 20 x 10mm (Main Body)
Product Weight	0.02kg

### Important Notice

1. The Mac series with Thunderbolt miniDisplayPort (Mid 2010 onwards) only supports 1920x1080 due to the inherent resolution limitations of the device.
2. DisplayPort to HDMI cannot be used in reverse.
3. Supports 4K (3840x2160) output up to 30Hz, not compatible with 4K60Hz.
4. Requires a 4K-compatible TV or display.
5. Does not support DP++ Mode. if you are using docking station, we suggest to choose Active DP to HDMI adapter. Please see the table in the following.